

50 mV/g 多用途加速度计

		
型号列	AC117 系	AC118 系列
描述	50mV/g 多用途加速度计, 接头/线缆,顶端输出	50mV/g 多用途加速度计, 接头/线缆,侧端输出
灵敏度	50 mV/g	50 mV/g
3dB 频响	1.0-12500 Hz	1.0-10000 Hz
动态范围	± 100 g, 峰值	± 100 g, 峰值
激励电压	18~30 VDC	18~30 VDC
温度范围	-50~121°C	-50~121°C
外壳原料	316L 不锈钢	316L 不锈钢
接头	2 Pin MIL-C-5015	2 Pin MIL-C-5015
最高温度	121°C	121°C

100 mV/g 小型加速度计

				
型号列	AC240 系	AC140 系列	AC244 系列	AC144 系列
描述	100mV/g 高性能小型加速度计,高频, 线缆,顶端输出	100mV/g 低成本小型加速度计, 线缆,顶端输出	100mV/g 高性能小型加速度计,高频, 线缆,侧端输出	100 mV/g 低成本小型加速度计, 线缆,侧端输出
灵敏度	100 mV/g	100 mV/g	100 mV/g	100 mV/g
3dB 频响	0.6-25000 Hz	0.5-15000 Hz	0.6-15000 Hz	0.6-10000 Hz
动态范围	± 50 g, 峰值	± 50 g, 峰值	± 50 g, 峰值	+50 g, 峰值
激励电压	18~30 VDC	18~30 VDC	18~30 VDC	18~30 VDC
温度范围	-50~121°C	-50~121°C	-50~121°C	-50~121°C
外壳材料	316L 不锈钢	316L 不锈钢	316L 不锈钢	316L 不锈钢
接头	2 Pin Mini-MIL	2 Pin MIL-C-5015	2 Pin Mini-MIL	2 Pin Mini-MIL
最高温度	121°C	121°C	121°C	121°C